



# ACRYLIC PAINT 001

## Acrylic facade paint

<b>Areas of application:</b>	Paint on the basis of water dispersion of acrylic resin, intended for painting facades and interiors. Incorporated in the TURBO thermal insulation systems by KREISEL
<b>Product features:</b>	Waterproof Frost-proof Good coverage UV-resistant Efficient Environmentally friendly Universal
<b>Material base:</b>	<ul style="list-style-type: none"> <li>• Water dispersion of acrylic polymer</li> <li>• Mineral fillers</li> <li>• Refining agents</li> <li>• Pigments</li> <li>• Water</li> </ul>
<b>Application:</b>	
<b>Conditions for application:</b>	Apply in temperatures from +5°C to +25°C, these temperature refer to air, groundwork and product temperature. Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.
<b>Surface:</b>	Reinforce absorbent and dusting surfaces with GRUNTOLIT-W 301 Eradicate all expressions of biological aggression on the groundwork using the SEPTOBUD 1008 solution. Repair all cracked and scratched surfaces with the 428 leveling grout or other, suitable for the groundwork type. The grout in the repaired sites must be completely dry and fixed. Cover all surfaces which are not intended for painting before the application of primers
<b>Types of substrate:</b>	<p><b>Cement-lime plaster:</b> Prime with GRUNTOLIT-W 301 or EXPERT 6</p> <p><b>Gypsum plaster:</b> prime with GRUNTOLIT-SG 302</p> <p><b>Concrete, reinforced concrete:</b> Prime with GRUNTOLIT-W 301 or EXPERT 6</p> <p><b>Fresh mineral plaster:</b></p> <p><b>Old thin-layer mineral and dispersion plasters:</b> Prime with GRUNTOLIT-W 301 or EXPERT 6</p> <p><b>Plasterboards:</b> Prime with GRUNTOLIT-W 301 or EXPERT 6</p>
<b>Preparation:</b>	Ready-to-use product. Do not dilute with water or mix with other materials. Mix thoroughly before use. Before applying, check if the color matches your order.
<b>Application:</b>	Apply the paint with a roller, brush or using a spray-application unit Average drying up time of one layer is 12 hours.
<b>Notes:</b>	Protect against precipitation, excessive sun rays, wind and frost during application and drying The use of scaffolding covers is recommended Paint in a continuous manner on one surface, do not allow any parts of the painted surface to dry out in the process to avoid visible lines Use paint from one production batch on one surface Apply the next layer after a minimum of 12 hours of drying of the previous layer Adverse conditions (high humidity, low temperature) can considerably extend the drying time.
<b>Storage:</b>	Maximally 12 months In dry areas and in non-damaged factory packaging, at temperatures from +5°C to +25°C.



# ACRYLIC PAINT 001

## Acrylic facade paint

### Technical data

<b>Consumption</b>	from 0.15 to 0.25 l/m <sup>2</sup>
<b>Density</b>	c.a. 1.45 g/cm <sup>3</sup>
<b>Coat resistance to wet-scrubbing</b>	≥ 5000 cycles
<b>Vapor-permeability</b>	≥ 140 g/m <sup>2</sup> 24h

### General notes:

This sheet supersedes all previous versions. The information included in this technical sheet represents the current knowledge and practical experience. The information sheet contains general information only and shall not be construed as any basis for manufacturer liability for performance and use. Differences and specific execution conditions may occur. The product is to be used according to the required level of technical knowledge and OHS principles. Avoid skin contact and protect the eyes. In the case of eye contact, wash the eyes abundantly with clean water and seek medical assistance. The use of gloves, goggles and protective clothing is recommended.